



Features:

- Support DAC/ADC Interface
- 16-bit Digital-to-Analog Converter
- 16-bit up to 10-kSPS ADC
- Internal Monitoring Hardware Information
- EtherCAT Conformance test tool verified
- Operating Temperature -20 to +70 °C

Specifications

Analog Input		Analog Output	
Channels	4 (Differential)	Channels	4
Input Type	Voltage (V)	Output Type	Voltage (V, mV), Current (mA)
Input Range	± 22 V; ± 20 V; ± 11 V; ± 10 V; ± 5 V; 0 V - 22V; 0 V - 20 V; 0 V - 11V; 0 V - 10 V	Output Current	0 mA - 24 mA; 3.5 mA - 23.5 mA; 0 mA - 20 mA; 4 mA - 20 mA; ± 24 mA
Input Impedance	Constant resistive ≥ 1 M Ω	Output Voltage	0 V - 5 V; 0 V - 10 V; ± 5 V; ± 10 V; - 0 V - 6 V; 0 V - 12 V; ± 6 V; ± 12 V
Overvoltage Protection	Up to ± 24 V	Resolution	16-bit with accuracy $\pm 0.1\%$ FSR@25°C
Resolution	16-bit with accuracy $\pm 0.2\%$ FSR @25°C	Slew Rate	Configurable (Option)
Sample Rate	Max. 10 kSPS	Drift	± 10 ppm/°C
General			
Connector	Euroblock Push-in Terminal		
Connector Color	Analog Input: Green; Analog Output: Orange; Negative: Black; Null: Gray;		
Protocol	EtherCAT (RJ-45 x 2)		
Ethernet Standard	IEEE 802.3		
Transmission Rate	100Mbps		
Power Connector	6-pin Power Input/Output		
Power Requirement	+19 to +50VDC Power Input (Typ. +24VDC@200mA)		
Power Consumption	4.8 W		
LED Indicator	PWR, RUN, LINK, ERROR, Analog Input/Output status		
Certifications	CE, FCC, VCCI		
Environment			
Operating Temperature	-20 to +70 °C		
Storage Temperature	-40~85°C		
Relative Humidity	95% (non-condense)		
Hardware			
Dimension	107.45 x 66 x 30mm (Without DIN-Rail)		
Weight	245 g		
Installation	DIN-Rail Mounting		
Internal Monitoring	Temperature, Voltage, Current		

Ordering Information

QEC-R00A44S-N	EtherCAT Slave 4-ch Analog Input and 4-ch Analog Output Module
QEC-R11A44S-N	EtherCAT Slave 4-ch Analog Input and 4-ch Analog Output Module/PoE
QEC-R11A44S-C	EtherCAT Slave 4-ch Analog Input and 4-ch Analog Output Module/PoE (Coating)

* For detailed ordering information, please contact our sales staff or view the user manual.

Dimension

